



SAFETY DATA SHEET

Issue Date 01-Jun-2015

Revision Date 30-May-2018

Version 4

1. IDENTIFICATION

Product identifier

Product Name UNIGLAZE CERULEAN BLUE LF

Other means of identification

Product Code UGLZ5010

UN/ID no. UN1993

Synonyms UGLZ501001, UGLZ501003, UGLZ501004, UGLZ501005, UGLZ501007, UGLZ501008, UGLZ501009, UGLZ501010, UGLZ501012, UGLZ501013, UGLZ501014, UGLZ501015, UGLZ501016, UGLZ501017, UGLZ501019, UGLZ501020, UGLZ501021, UGLZ501022, UGLZ501023, UGLZ501033, UGLZ501035, UGLZ501055

Recommended use of the chemical and restrictions on use

Recommended Use Restricted to professional users.

Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address

Rutland Group
10021 Rodney Street
Pineville, NC 28134
Tel: 704-553-0046

E-mail address product_safety@rutlandinc.com

Emergency telephone number

Emergency Telephone Chemtrec 1-800-424-9300
INFOTRAC 1-352-323-3500

Specific treatment (see .? on this label)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

If skin irritation occurs: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

Rinse mouth

In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

May be harmful in contact with skin

Toxic to aquatic life with long lasting effects

Harmful to aquatic life

Unknown acute toxicity

53.1% of the mixture has not undergone testing for acute toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

Chemical Name	CAS No.	Weight-%	Trade Secret
EPOXY RESIN	25036-25-3	30 - 60	*
2-BUTOXYETHANOL	111-76-2	5 - 10	*
1 METHOXY 2 PROPANOL ACETATE	108-65-6	3 - 7	*
SOLVENT NAPHTHA (PETROLEUM) LIGHT AROMATIC	64742-95-6	3 - 7	*
TITANIUM DIOXIDE	13463-67-7	3 - 7	*
1,2,4-TRIMETHYLBENZENE	95-63-6	1 - 5	*
2-(2-Butoxyethoxy)ethyl acetate	124-17-4	1 - 5	*
NAPHTHA (PETROLEUM) HEAVY AROMATIC	64742-94-5	1 - 5	*
NAPHTHALENE	91-20-3	0.1 - 1	*
CUMENE	98-82-8	0.1 - 1	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General advice	Call 911 or emergency medical service. Remove and isolate contaminated clothing and shoes.
Eye contact	In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
Skin contact	Wash skin with soap and water.
Inhalation	Move victim to fresh air. If breathing is irregular or stopped, administer artificial respiration. Administer oxygen if breathing is difficult.
Ingestion	Do NOT induce vomiting. Rinse mouth. Drink plenty of water. Never give anything by mouth to an unconscious person. Call a physician.
Self-protection of the first aider	Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

Most important symptoms and effects, both acute and delayed

Symptoms No information available.

Indication of any immediate medical attention and special treatment needed

Note to physicians Keep victim warm and quiet.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Dry chemical, CO₂, water spray or regular foam. Water spray, fog or regular foam. Use water spray or fog; do not use straight streams. Move containers from fire area if you can do it without risk.

Unsuitable extinguishing media CAUTION: All these products have a very low flash point. Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Those substances designated with a "P" may polymerize explosively when heated or involved in a fire. Runoff to sewer may create fire or explosion hazard. Substance may be transported hot.

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Stop leak if you can do it without risk.

Other Information Water spray may reduce vapor; but may not prevent ignition in closed spaces.

Environmental precautions

Environmental precautions Prevent entry into waterways, sewers, basements or confined areas. See section 12 for additional ecological information.

Methods and material for containment and cleaning up

Methods for containment A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Dike far ahead of liquid spill for later disposal.

Methods for cleaning up Use clean non-sparking tools to collect absorbed material.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Ensure adequate ventilation, especially in confined areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep tightly closed in a dry and cool place
Keep in properly labeled containers
Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity)

Incompatible materials None known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
2-BUTOXYETHANOL 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m ³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m ³ (vacated) S* S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m ³
TITANIUM DIOXIDE 13463-67-7	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust (vacated) TWA: 10 mg/m ³ total dust	IDLH: 5000 mg/m ³
1,2,4-TRIMETHYLBENZENE 95-63-6	-	-	TWA: 25 ppm TWA: 125 mg/m ³
NAPHTHALENE 91-20-3	TWA: 10 ppm S*	TWA: 10 ppm TWA: 50 mg/m ³ (vacated) TWA: 10 ppm (vacated) TWA: 50 mg/m ³ (vacated) STEL: 15 ppm (vacated) STEL: 75 mg/m ³	IDLH: 250 ppm TWA: 10 ppm TWA: 50 mg/m ³ STEL: 15 ppm STEL: 75 mg/m ³
CUMENE 98-82-8	TWA: 50 ppm	TWA: 50 ppm TWA: 245 mg/m ³ (vacated) TWA: 50 ppm (vacated) TWA: 245 mg/m ³ (vacated) S* S*	IDLH: 900 ppm TWA: 50 ppm TWA: 245 mg/m ³

NIOSH IDLH *Immediately Dangerous to Life or Health*

Chemical Name	Alberta OEL	British Columbia OEL	Manitoba OEL	New Brunswick OEL
2-BUTOXYETHANOL 111-76-2	TWA: 20 ppm TWA: 97 mg/m ³	TWA: 20 ppm	TWA: 20 ppm	TWA: 25 ppm TWA: 121 mg/m ³
1 METHOXY 2 PROPANOL ACETATE 108-65-6	-	TWA: 50 ppm STEL: 75 ppm	-	-
TITANIUM DIOXIDE 13463-67-7	TWA: 10 mg/m ³	TWA: 10 mg/m ³ TWA: 3 mg/m ³	TWA: 10 mg/m ³	TWA: 10 mg/m ³
NAPHTHALENE 91-20-3	TWA: 10 ppm TWA: 52 mg/m ³ STEL: 15 ppm STEL: 79 mg/m ³ Skin	TWA: 10 ppm STEL: 15 ppm Skin	TWA: 10 ppm	TWA: 10 ppm TWA: 52 mg/m ³ STEL: 15 ppm STEL: 79 mg/m ³
CUMENE 98-82-8	TWA: 50 ppm TWA: 246 mg/m ³	TWA: 25 ppm STEL: 75 ppm	TWA: 50 ppm	TWA: 50 ppm TWA: 246 mg/m ³

Chemical Name	Newfoundland OEL	Northwest Territories OEL	Nova Scotia OEL	Nunavut OEL
2-BUTOXYETHANOL 111-76-2	TWA: 20 ppm	TWA: 20 ppm STEL: 30 ppm	TWA: 20 ppm	TWA: 20 ppm STEL: 30 ppm
TITANIUM DIOXIDE 13463-67-7	TWA: 10 mg/m ³	TWA: 10 mg/m ³ STEL: 20 mg/m ³	TWA: 10 mg/m ³	TWA: 10 mg/m ³ STEL: 20 mg/m ³
NAPHTHALENE 91-20-3	TWA: 10 ppm	TWA: 10 ppm STEL: 15 ppm	TWA: 10 ppm	TWA: 10 ppm STEL: 15 ppm
CUMENE 98-82-8	TWA: 50 ppm	TWA: 50 ppm STEL: 74 ppm	TWA: 50 ppm	TWA: 50 ppm STEL: 74 ppm

Chemical Name	Ontario OEL	Prince Edward Island OEL	Quebec OEL	Saskatchewan OEL	Yukon OEL
2-BUTOXYETHANOL 111-76-2	TWA: 20 ppm	TWA: 20 ppm	TWA: 20 ppm TWA: 97 mg/m ³	TWA: 20 ppm STEL: 30 ppm	STEL: 150 ppm STEL: 720 mg/m ³ TWA: 50 ppm TWA: 240 mg/m ³
1 METHOXY 2 PROPANOL ACETATE 108-65-6	TWA: 50 ppm TWA: 270 mg/m ³	-	-	-	-
TITANIUM DIOXIDE	TWA: 10 mg/m ³	TWA: 10 mg/m ³	TWA: 10 mg/m ³	TWA: 10 mg/m ³	STEL: 20 mg/m ³

13463-67-7				STEL: 20 mg/m ³	TWA: 30 mppcf TWA: 10 mg/m ³
NAPHTHALENE 91-20-3	TWA: 10 ppm STEL: 15 ppm Skin	TWA: 10 ppm	TWA: 10 ppm TWA: 52 mg/m ³ STEL: 15 ppm STEL: 79 mg/m ³	TWA: 10 ppm STEL: 15 ppm	STEL: 15 ppm STEL: 75 mg/m ³ TWA: 10 ppm TWA: 50 mg/m ³
CUMENE 98-82-8	TWA: 50 ppm	TWA: 50 ppm	TWA: 50 ppm TWA: 246 mg/m ³	TWA: 50 ppm STEL: 74 ppm	STEL: 75 ppm STEL: 365 mg/m ³ TWA: 50 ppm TWA: 245 mg/m ³

Other Information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls

Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin and body protection

Wear protective gloves and protective clothing.

Respiratory protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

General Hygiene Considerations

When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	liquid	Odor	Aromatic
Appearance	viscous	Odor threshold	No information available
Color	colored		

Property	Values	Remarks • Method
pH	7	
Melting point/freezing point	No information available	
Boiling point / boiling range	149 °C / 300 °F	
Flash point	52 °C / 126 °F	Tag Closed Cup
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability limit:	No information available	
Lower flammability limit:	No information available	
Vapor pressure	No information available	
Vapor density	No information available	
Specific Gravity	1.1	
Water solubility	Insoluble in water	
Solubility in other solvents	No information available	
Partition coefficient	No information available	
Autoignition temperature	No information available	
Decomposition temperature	No information available	
Kinematic viscosity	No information available	
Dynamic viscosity	No information available	
Explosive properties	No information available	
Oxidizing properties	No information available	

Other Information

Softening point	No information available
Molecular weight	No information available
VOC Content	600 theoretical g/L
Density	No information available
Bulk density	No information available

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

None known based on information supplied.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	No data available
Inhalation	No data available.
Eye contact	No data available.
Skin contact	No data available.
Ingestion	No data available.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
2-BUTOXYETHANOL 111-76-2	= 470 mg/kg (Rat)	= 99 mg/kg (Rabbit)	= 450 ppm (Rat) 4 h
1 METHOXY 2 PROPANOL ACETATE 108-65-6	= 8532 mg/kg (Rat)	> 5 g/kg (Rabbit)	-
SOLVENT NAPHTHA (PETROLEUM) LIGHT AROMATIC 64742-95-6	= 8400 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 3400 ppm (Rat) 4 h
TITANIUM DIOXIDE 13463-67-7	> 10000 mg/kg (Rat)	-	-
1,2,4-TRIMETHYLBENZENE 95-63-6	= 3280 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 18 g/m ³ (Rat) 4 h
2-(2-Butoxyethoxy)ethyl acetate 124-17-4	= 6500 mg/kg (Rat)	= 14500 mg/kg (Rabbit)	= 72500 mg/m ³ (Rat) 4 h
NAPHTHA (PETROLEUM) HEAVY AROMATIC 64742-94-5	> 5000 mg/kg (Rat)	> 2 mL/kg (Rabbit)	> 590 mg/m ³ (Rat) 4 h
NAPHTHALENE 91-20-3	= 1110 mg/kg (Rat) = 490 mg/kg (Rat)	(= 1120 mg/kg (Rabbit) > 20 g/kg (Rabbit)	> 340 mg/m ³ (Rat) 1 h
CUMENE 98-82-8	= 1400 mg/kg (Rat)	= 12300 µL/kg (Rabbit)	> 3577 ppm (Rat) 6 h = 39000 mg/m ³ (Rat) 4 h

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
2-BUTOXYETHANOL 111-76-2	A3	Group 3	-	-
TITANIUM DIOXIDE 13463-67-7	-	Group 2B	-	X
NAPHTHALENE 91-20-3	A3	Group 2B	Reasonably Anticipated	X
CUMENE 98-82-8	-	Group 2B	Reasonably Anticipated	X

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2A - Probably Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Not classifiable as a human carcinogen

NTP (National Toxicology Program)

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity No information available.

STOT - single exposure	No information available.
STOT - repeated exposure	No information available.
Chronic toxicity	May cause adverse effects on the bone marrow and blood-forming system. May cause adverse liver effects.
Target Organ Effects	blood, Central nervous system, Eyes, Hematopoietic System, kidney, liver, Lungs, Respiratory system, Skin.
Aspiration hazard	No information available.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)	1735 mg/kg
ATEmix (dermal)	3023 mg/kg
ATEmix (inhalation-gas)	No information available
ATEmix (inhalation-dust/mist)	5.8 mg/l
ATEmix (inhalation-vapor)	No information available mg/l

12. ECOLOGICAL INFORMATION**Ecotoxicity**

Toxic to aquatic life with long lasting effects

63 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

Contaminated packaging Do not reuse container.

US EPA Waste Number D001 U055 U140 U165 U239

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
XYLENE 1330-20-7	-	Included in waste stream: F039	-	U239
NAPHTHALENE 91-20-3	U165	Included in waste streams: F024, F025, F034, F039, K001, K035, K060, K087, K145	-	U165
CUMENE 98-82-8	-	-	-	U055
ETHYL BENZENE 100-41-4	-	Included in waste stream: F039	-	-
ISOBUTYL ALCOHOL 78-83-1	U140	Included in waste streams: F005, F039	-	U140

Chemical Name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
NAPHTHALENE 91-20-3	-	-	Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	-

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
NAPHTHALENE 91-20-3	Toxic
CUMENE 98-82-8	Toxic Ignitable

14. TRANSPORT INFORMATION

DOT

UN/ID no.	UN1993
Proper shipping name	Flammable liquids, n.o.s.
Hazard Class	3
Packing Group	III
Reportable Quantity (RQ)	Xylenes mixed isomers: RQ kg= 19739.13
Special Provisions	B1, B52, IB3, T4, TP1, TP29
Description	UN1993, Flammable liquids, n.o.s. (1 METHOXY 2 PROPANOL ACETATE, 1,2,4-TRIMETHYLBENZENE), 3, III, RQ
Emergency Response Guide Number	128

TDG

UN/ID no.	UN1993
Proper shipping name	Flammable liquid, n.o.s.
Hazard Class	3
Packing Group	III
Description	UN1993, Flammable liquid, n.o.s. (1 METHOXY 2 PROPANOL ACETATE, 1,2,4-TRIMETHYLBENZENE), 3, III

MEX

UN/ID no.	UN1993
Proper shipping name	Flammable liquid, n.o.s.
Hazard Class	3
Packing Group	III
Description	UN1993, Flammable liquid, n.o.s. (1 METHOXY 2 PROPANOL ACETATE, 1,2,4-TRIMETHYLBENZENE), 3, III

ICAO (air)

UN/ID no.	UN1993
Proper shipping name	Flammable liquid, n.o.s.
Hazard Class	3
Packing Group	III
Special Provisions	A3
Description	UN1993, Flammable liquid, n.o.s. (1 METHOXY 2 PROPANOL ACETATE, 1,2,4-TRIMETHYLBENZENE), 3, III

IATA

UN/ID no.	UN1993
Hazard Class	3
Packing Group	III
ERG Code	3L
Special Provisions	A3
Description	UN1993, Flammable liquid, n.o.s. (1 METHOXY 2 PROPANOL ACETATE, 1,2,4-TRIMETHYLBENZENE), 3, III

IMDG

UN/ID no.	UN1993
Hazard Class	3
Packing Group	III
EmS-No.	F-E, S-E
Special Provisions	223, 274, 955
Description	UN1993, Flammable liquid, n.o.s. (1 METHOXY 2 PROPANOL ACETATE, 1,2,4-TRIMETHYLBENZENE), 3, III, (52°C c.c.)

RID

UN/ID no.	UN1993
Proper shipping name	Flammable liquid, n.o.s.
Hazard Class	3

Packing Group	III
Classification code	F1
Description	UN1993, Flammable liquid, n.o.s. (1 METHOXY 2 PROPANOL ACETATE, 1,2,4-TRIMETHYLBENZENE), Environmentally Hazardous, 3, III

ADR

UN/ID no.	UN1993
Proper shipping name	Flammable liquid, n.o.s.
Hazard Class	3
Packing Group	III
Classification code	F1
Tunnel restriction code	(D/E)
Special Provisions	274, 601, 640E
Description	UN1993, Flammable liquid, n.o.s. (1 METHOXY 2 PROPANOL ACETATE, 1,2,4-TRIMETHYLBENZENE), Environmentally Hazardous, 3, III, (D/E)
Labels	3

ADN

UN Number	UN1993
Proper shipping name	Flammable liquid, n.o.s.
Hazard Class	3
Packing Group	III
Classification code	F1
Special Provisions	274, 601, 640E
Description	UN1993, Flammable liquid, n.o.s. (1 METHOXY 2 PROPANOL ACETATE, 1,2,4-TRIMETHYLBENZENE), Environmentally Hazardous, 3, III
Hazard label(s)	3
Limited quantity (LQ)	5 L
Ventilation	VE01

15. REGULATORY INFORMATION

International Inventories **On Inventory (Yes/No)**

TSCA	Yes
DSL/NDSL	Yes
EINECS/ELINCS	No
ENCS	No
IECSC	Yes
KECL	Yes
PICCS	Yes
AICS	Yes

Legend:

- TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory
- DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List
- EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
- ENCS** - Japan Existing and New Chemical Substances
- IECSC** - China Inventory of Existing Chemical Substances
- KECL** - Korean Existing and Evaluated Chemical Substances
- PICCS** - Philippines Inventory of Chemicals and Chemical Substances
- AICS** - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
2-BUTOXYETHANOL - 111-76-2	1.0
FELDSPAR - 68476-25-5	1.0
PIGMENT GREEN G-7 - 1328-53-6	1.0
1,2,4-TRIMETHYLBENZENE - 95-63-6	1.0
2-(2-Butoxyethoxy)ethyl acetate - 124-17-4	1.0
NAPHTHALENE - 91-20-3	0.1

SARA 311/312 Hazard Categories

Acute health hazard	No
Chronic Health Hazard	No
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
NAPHTHALENE 91-20-3	100 lb	X	X	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
NAPHTHALENE 91-20-3	100 lb 1 lb	-	RQ 100 lb final RQ RQ 45.4 kg final RQ 1 lb final RQ RQ 0.454 kg final RQ
CUMENE 98-82-8	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical Name	California Proposition 65
NAPHTHALENE - 91-20-3	Carcinogen
CUMENE - 98-82-8	Carcinogen
ETHYL BENZENE - 100-41-4	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
2-BUTOXYETHANOL 111-76-2	X	X	X
FELDSPAR 68476-25-5	X	-	X
PIGMENT GREEN G-7 1328-53-6	X	-	X
1,2,4-TRIMETHYLBENZENE 95-63-6	X	X	X
2-(2-Butoxyethoxy)ethyl acetate 124-17-4	X	-	X
XYLENE 1330-20-7	X	X	X
NAPHTHALENE 91-20-3	X	X	X
CUMENE 98-82-8	X	X	X
ETHYL BENZENE 100-41-4	X	X	X
ISOBUTYL ALCOHOL 78-83-1	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA	Health hazards 2	Flammability 2	Instability 0	Physical and Chemical Properties -
HMIS	Health hazards 2	Flammability 2	Physical hazards 0	Personal protection X

Issue Date 01-Jun-2015
 Revision Date 30-May-2018
 Revision Note
 SDS sections updated 1 3 9

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet