



SAFETY DATA SHEET

Issue Date 01-Jun-2015

Revision Date 17-Jul-2018

Version 5

1. IDENTIFICATION

Product identifier

Product Name UNIGLAZE P300C BLUE

Other means of identification

Product Code UGLZP300C

UN/ID no. UN1993

Synonyms UGLZP300C01, UGLZP300C03, UGLZP300C04, UGLZP300C05, UGLZP300C07, UGLZP300C08, UGLZP300C09, UGLZP300C10, UGLZP300C12, UGLZP300C13, UGLZP300C14, UGLZP300C15, UGLZP300C16, UGLZP300C17, UGLZP300C19, UGLZP300C20, UGLZP300C21, UGLZP300C22, UGLZP300C23, UGLZP300C33, UGLZP300C35, UGLZP300C55

Recommended use of the chemical and restrictions on use

Recommended Use Restricted to professional users.

Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address

Rutland Group
10021 Rodney Street
Pineville, NC 28134
Tel: 704-553-0046

E-mail address product_safety@rutlandinc.com

Emergency telephone number

Emergency Telephone INFOTRAC 1-352-323-3500

IF exposed or concerned: Get medical advice/attention
 Specific treatment (see .? on this label)
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 If eye irritation persists: Get medical advice/attention
 If skin irritation or rash occurs: Get medical advice/attention
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
 Wash contaminated clothing before reuse
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 Rinse mouth
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
 Do NOT induce vomiting
 In case of fire: Use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up
 Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

May be harmful in contact with skin
 Harmful to aquatic life with long lasting effects
 Harmful to aquatic life

Unknown acute toxicity

56.1% of the mixture has not undergone testing for acute toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

Chemical Name	CAS No.	Weight-%	Trade Secret
EPOXY RESIN	25036-25-3	30 - 60	*
SOLVENT NAPHTHA (PETROLEUM) LIGHT AROMATIC	64742-95-6	7 - 13	*
2-BUTOXYETHANOL	111-76-2	5 - 10	*
1 METHOXY 2 PROPANOL ACETATE	108-65-6	5 - 10	*
1,2,4-TRIMETHYLBENZENE	95-63-6	1 - 5	*
2-(2-Butoxyethoxy)ethyl acetate	124-17-4	1 - 5	*
CUMENE	98-82-8	0.1 - 1	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General advice	Call 911 or emergency medical service. Remove and isolate contaminated clothing and shoes.
Eye contact	In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
Skin contact	Wash skin with soap and water.
Inhalation	Move victim to fresh air. If breathing is irregular or stopped, administer artificial respiration. Administer oxygen if breathing is difficult.
Ingestion	Do NOT induce vomiting. Rinse mouth. Drink plenty of water. If symptoms persist, call a physician.
Self-protection of the first aider	Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

Most important symptoms and effects, both acute and delayed

Symptoms No information available.

Indication of any immediate medical attention and special treatment needed

Note to physicians Keep victim warm and quiet.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Dry chemical, CO₂, water spray or regular foam. Water spray, fog or regular foam. Use water spray or fog; do not use straight streams. Move containers from fire area if you can do it without risk.

Unsuitable extinguishing media CAUTION: All these products have a very low flash point. Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Those substances designated with a "P" may polymerize explosively when heated or involved in a fire. Runoff to sewer may create fire or explosion hazard. Substance may be transported hot.

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Stop leak if you can do it without risk.

Other Information Water spray may reduce vapor; but may not prevent ignition in closed spaces.

Environmental precautions

Environmental precautions Prevent entry into waterways, sewers, basements or confined areas. See section 12 for additional ecological information.

Methods and material for containment and cleaning up

Methods for containment A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Dike far ahead of liquid spill for later disposal.

Methods for cleaning up Use clean non-sparking tools to collect absorbed material.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Ensure adequate ventilation, especially in confined areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep tightly closed in a dry and cool place
Keep in properly labeled containers
Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity)

Incompatible materials None known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
2-BUTOXYETHANOL 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m ³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m ³ (vacated) S* S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m ³
1,2,4-TRIMETHYLBENZENE 95-63-6	-	-	TWA: 25 ppm TWA: 125 mg/m ³
CUMENE 98-82-8	TWA: 50 ppm	TWA: 50 ppm TWA: 245 mg/m ³ (vacated) TWA: 50 ppm (vacated) TWA: 245 mg/m ³ (vacated) S* S*	IDLH: 900 ppm TWA: 50 ppm TWA: 245 mg/m ³

NIOSH IDLH *Immediately Dangerous to Life or Health*

Chemical Name	Alberta OEL	British Columbia OEL	Manitoba OEL	New Brunswick OEL
2-BUTOXYETHANOL 111-76-2	TWA: 20 ppm TWA: 97 mg/m ³	TWA: 20 ppm	TWA: 20 ppm	TWA: 25 ppm TWA: 121 mg/m ³
1 METHOXY 2 PROPANOL ACETATE 108-65-6	-	TWA: 50 ppm STEL: 75 ppm	-	-
CUMENE 98-82-8	TWA: 50 ppm TWA: 246 mg/m ³	TWA: 25 ppm STEL: 75 ppm	TWA: 50 ppm	TWA: 50 ppm TWA: 246 mg/m ³

Chemical Name	Newfoundland OEL	Northwest Territories OEL	Nova Scotia OEL	Nunavut OEL
2-BUTOXYETHANOL 111-76-2	TWA: 20 ppm	TWA: 20 ppm STEL: 30 ppm	TWA: 20 ppm	TWA: 20 ppm STEL: 30 ppm
CUMENE 98-82-8	TWA: 50 ppm	TWA: 50 ppm STEL: 74 ppm	TWA: 50 ppm	TWA: 50 ppm STEL: 74 ppm

Chemical Name	Ontario OEL	Prince Edward Island OEL	Quebec OEL	Saskatchewan OEL	Yukon OEL
2-BUTOXYETHANOL 111-76-2	TWA: 20 ppm	TWA: 20 ppm	TWA: 20 ppm TWA: 97 mg/m ³	TWA: 20 ppm STEL: 30 ppm	STEL: 150 ppm STEL: 720 mg/m ³ TWA: 50 ppm TWA: 240 mg/m ³
1 METHOXY 2 PROPANOL ACETATE 108-65-6	TWA: 50 ppm TWA: 270 mg/m ³	-	-	-	-
CUMENE 98-82-8	TWA: 50 ppm	TWA: 50 ppm	TWA: 50 ppm TWA: 246 mg/m ³	TWA: 50 ppm STEL: 74 ppm	STEL: 75 ppm STEL: 365 mg/m ³ TWA: 50 ppm TWA: 245 mg/m ³

Other Information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls

Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection

Tight sealing safety goggles.

Skin and body protection

Wear protective gloves and protective clothing.

Respiratory protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

General Hygiene Considerations

When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	liquid	Odor	Aromatic
Appearance	viscous	Odor threshold	No information available
Color	colored		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	7	
Melting point/freezing point	No information available	
Boiling point / boiling range	149 °C / 300 °F	
Flash point	52 °C / 126 °F	
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability limit:	No information available	
Lower flammability limit:	No information available	
Vapor pressure	No information available	
Vapor density	>1	
Specific Gravity	1.4	
Water solubility	Insoluble in water	
Solubility in other solvents	No information available	
Partition coefficient	No information available	
Autoignition temperature	No information available	
Decomposition temperature	No information available	
Kinematic viscosity	No information available	
Dynamic viscosity	No information available	
Explosive properties	No information available	
Oxidizing properties	No information available	

Other Information

Softening point	No information available
Molecular weight	No information available
VOC Content	<600 g/L
Density	No information available
Bulk density	No information available

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

None known based on information supplied.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	No data available
Inhalation	No data available.
Eye contact	No data available.
Skin contact	No data available.
Ingestion	No data available.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
SOLVENT NAPHTHA (PETROLEUM) LIGHT AROMATIC 64742-95-6	= 8400 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 3400 ppm (Rat) 4 h
2-BUTOXYETHANOL 111-76-2	= 470 mg/kg (Rat)	= 99 mg/kg (Rabbit)	= 450 ppm (Rat) 4 h = 486 ppm (Rat) 4 h
1 METHOXY 2 PROPANOL ACETATE 108-65-6	= 8532 mg/kg (Rat)	> 5 g/kg (Rabbit)	-
1,2,4-TRIMETHYLBENZENE 95-63-6	= 3280 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 18 g/m ³ (Rat) 4 h
2-(2-Butoxyethoxy)ethyl acetate 124-17-4	= 6500 mg/kg (Rat)	= 14500 mg/kg (Rabbit)	= 72500 mg/m ³ (Rat) 4 h
CUMENE 98-82-8	= 1400 mg/kg (Rat)	= 12300 µL/kg (Rabbit)	> 3577 ppm (Rat) 6 h = 39000 mg/m ³ (Rat) 4 h

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
2-BUTOXYETHANOL 111-76-2	A3	Group 3	-	-
CUMENE 98-82-8	-	Group 2B	Reasonably Anticipated	X

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Not classifiable as a human carcinogen

NTP (National Toxicology Program)

Known - Known Carcinogen

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity No information available.

STOT - single exposure No information available.

STOT - repeated exposure No information available.

Chronic toxicity May cause adverse effects on the bone marrow and blood-forming system. May cause adverse liver effects.

Target Organ Effects blood, Central nervous system, Eyes, Hematopoietic System, kidney, liver, Lungs, Respiratory system, Skin.

Aspiration hazard No information available.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)	1627 mg/kg
ATEmix (dermal)	2654 mg/kg
ATEmix (inhalation-gas)	No information available
ATEmix (inhalation-dust/mist)	5.2 mg/l
ATEmix (inhalation-vapor)	No information available mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life with long lasting effects

66.2 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

Contaminated packaging Do not reuse container.

US EPA Waste Number D001 U055 U140 U165 U239

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
XYLENE 1330-20-7	-	Included in waste stream: F039	-	U239
CUMENE 98-82-8	-	-	-	U055

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
CUMENE 98-82-8	Toxic Ignitable

14. TRANSPORT INFORMATION

DOT

UN/ID no.	UN1993
Proper shipping name	Flammable liquids, n.o.s.
Hazard Class	3
Packing Group	III
Reportable Quantity (RQ)	Xylenes mixed isomers: RQ kg= 19739.13
Special Provisions	B1, B52, IB3, T4, TP1, TP29
Description	UN1993, Flammable liquids, n.o.s. (1 METHOXY 2 PROPANOL ACETATE, 1,2,4-TRIMETHYLBENZENE), 3, III, RQ
Emergency Response Guide Number	128

TDG

UN/ID no.	UN1993
Proper shipping name	Flammable liquid, n.o.s.
Hazard Class	3
Packing Group	III
Description	UN1993, Flammable liquid, n.o.s. (1 METHOXY 2 PROPANOL ACETATE, 1,2,4-TRIMETHYLBENZENE), 3, III

MEX

UN/ID no.	UN1993
Proper shipping name	Flammable liquid, n.o.s.
Hazard Class	3
Packing Group	III
Description	UN1993, Flammable liquid, n.o.s. (1 METHOXY 2 PROPANOL ACETATE, 1,2,4-TRIMETHYLBENZENE), 3, III

ICAO (air)

UN/ID no.	UN1993
Proper shipping name	Flammable liquid, n.o.s.
Hazard Class	3
Packing Group	III
Special Provisions	A3
Description	UN1993, Flammable liquid, n.o.s. (1 METHOXY 2 PROPANOL ACETATE, 1,2,4-TRIMETHYLBENZENE), 3, III

IATA

UN/ID no.	UN1993
Hazard Class	3
Packing Group	III
ERG Code	3L
Special Provisions	A3
Description	UN1993, Flammable liquid, n.o.s. (1 METHOXY 2 PROPANOL ACETATE, 1,2,4-TRIMETHYLBENZENE), 3, III

IMDG

UN/ID no.	UN1993
Hazard Class	3
Packing Group	III
EmS-No.	F-E, S-E
Special Provisions	223, 274, 955
Description	UN1993, Flammable liquid, n.o.s. (1 METHOXY 2 PROPANOL ACETATE, 1,2,4-TRIMETHYLBENZENE), 3, III, (52°C c.c.)

RID

UN/ID no.	UN1993
Proper shipping name	Flammable liquid, n.o.s.
Hazard Class	3

Packing Group III
Classification code F1
Description UN1993, Flammable liquid, n.o.s. (1 METHOXY 2 PROPANOL ACETATE, 1,2,4-TRIMETHYLBENZENE), Environmentally Hazardous, 3, III

ADR

UN/ID no. UN1993
Proper shipping name Flammable liquid, n.o.s.
Hazard Class 3
Packing Group III
Classification code F1
Tunnel restriction code (D/E)
Special Provisions 274, 601, 640E
Description UN1993, Flammable liquid, n.o.s. (1 METHOXY 2 PROPANOL ACETATE, 1,2,4-TRIMETHYLBENZENE), Environmentally Hazardous, 3, III, (D/E)
Labels 3

ADN

Proper shipping name Flammable liquid, n.o.s.
Hazard Class 3
Packing Group III
Classification code F1
Special Provisions 274, 601, 640E
Description UN1993, Flammable liquid, n.o.s. (1 METHOXY 2 PROPANOL ACETATE, 1,2,4-TRIMETHYLBENZENE), Environmentally Hazardous, 3, III
Hazard label(s) 3
Limited quantity (LQ) 5 L
Ventilation VE01

15. REGULATORY INFORMATION

<u>International Inventories</u>	On Inventory (Yes/No)
---	------------------------------

TSCA	Yes
DSL/NDSL	Yes
EINECS/ELINCS	Yes
ENCS	No
IECSC	Yes
KECL	Yes
PICCS	Yes
AICS	No

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

US Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
2-BUTOXYETHANOL - 111-76-2	1.0
1,2,4-TRIMETHYLBENZENE - 95-63-6	1.0
2-(2-Butoxyethoxy)ethyl acetate - 124-17-4	1.0

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	No
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
CUMENE 98-82-8	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ

US State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical Name	California Proposition 65
CUMENE - 98-82-8	Carcinogen
1,2-BENZENEDICARBOXYLIC ACID DIC9-11 BRANCHED ALKYLESTERS, C10 RICH - 68515-49-1	Developmental

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
2-BUTOXYETHANOL 111-76-2	X	X	X
1,2,4-TRIMETHYLBENZENE 95-63-6	X	X	X
2-(2-Butoxyethoxy)ethyl acetate 124-17-4	X	-	X
XYLENE 1330-20-7	X	X	X
CUMENE 98-82-8	X	X	X
ETHYL LACTATE 97-64-3	X	X	X
1,2-BENZENEDICARBOXYLIC ACID DIC9-11 BRANCHED ALKYLESTERS, C10 RICH 68515-49-1	-	-	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA	Health hazards 2	Flammability 2	Instability 0	Physical and Chemical Properties -
HMIS	Health hazards 2	Flammability 2	Physical hazards 0	Personal protection X

Issue Date 01-Jun-2015

Revision Date 17-Jul-2018

Revision Note

SDS sections updated 3

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet